



Smeermiddelenindustrie • Schmiermittelindustrie

Lube-oil industry • Industrie Lubrifiant

DE OLIEBRON LUBRICATION(GD) CO.,LTD

TEL: +86 4008801150

Internet: <http://www.deoliebron.com>

E-mail: [info@deoliebron.com](mailto:info@deoliebron.com)

## SynthGold 0W40

### Description

A modern, Fully synthetic, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### Application

A universal, special composed fully synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

### Specifications

Performance level:

ACEA A3/B4

API SP

BMW Longlife-04

MB 229.3/229.5

Porsche A40

VW 502.00/505.00

### Typicals

Density at 20°C, kg/l	0,841
Viscosity -35 °C, mPa.s	5107
Viscosity 40 °C, mm <sup>2</sup> /s	73,57
Viscosity 100 °C, mm <sup>2</sup> /s	13,57
Viscosity Index	190
Flash Point COC, °C	230
Pour Point, °C	-45
Total Base Number, mgKOH/g	12,2
Sulphate Ash, %	1,12
HTHS viscosity@150, mPa.s	3,8