



Smeermiddelenindustrie • Schmiermittelindustrie

DE OLIEBRON LUBRICATION(GD) CO.,LTD

TEL: +86 4008801150

Internet: <http://www.deoliebron.com>

E-mail: info@deoliebron.com

Lube-oil industry • Industrie Lubrifiant

SynthBenz FE 0W20

Description

A modern, fully synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to

obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

A modern fuel economy, special composed synthetic motor oil suitable for use in petrol and diesel engines of passenger cars and delivery vans. This oil is fully backward compatible with BMW Longlife-14 FE+.

Specifications

ACEA C5

API SP Resource Conserving

ILSAC GF-6A

Meets the requirements of:

BMW Longlife-17 FE+

Ford WSS-M2C947-B1 / WSS-M2C962-A1

Jaguar Land Rover STJLR.03.5006

MB 229.71

Opel OV0401547

Chrysler MS-12145

Fiat 9.55535-GSX

Typicals

Density at 20 °C, kg/l	0,840
Viscosity -35 °C, mPa.s	4960
Viscosity 40 °C, mm ² /s	39,73
Viscosity 100 °C, mm ² /s	8,114
Viscosity Index	184
Flash Point COC, °C	236
Pour Point, °C	-42
Total Base Number, mgKOH/g	9,22
Sulphate Ash, %	0,78
HTHS viscosity@150, mPa.s	2,7