



Smeermiddelenindustrie • Schmiermittelindustrie

Lube-oil industry • Industrie Lubrifiant

DE OLIEBRON LUBRICATION(GD) CO.,LTD

TEL: +86 4008801150

Internet: <http://www.deoliebron.com.cn>

E-mail: info@deoliebron.com

SynthLub 10W40

Description

This motor oil is produced with high quality solvent refined base oils and a number of additives, to obtain the following properties:

- a high detergency and dispersion power
- a strong resistance against oxidation
- effective in preventing from wear, corrosion and foam
- a high and stable viscosity index

Application

Suitable lubricating oil for gasoline engines under light service conditions, moreover for diesel engines of passenger cars and for light delivery vans in light service. Not applicable for turbo-charging diesel engines for which a minimum API CG level oil is required.

Specifications

Performance level:
API SN plus

Typicals

| | |
|--------------------------------------|-------|
| Density at 20 °C, kg/l | 0,861 |
| Viscosity -25 °C, mPa.s | 6462 |
| Viscosity 40 °C, mm ² /s | 101,7 |
| Viscosity 100 °C, mm ² /s | 14,64 |
| Viscosity Index | 149 |
| Flash Point COC, °C | 236 |
| Pour Point, °C | -36 |
| Total Base Number, mgKOH/g | 7,5 |
| Sulphate Ash, % | -- |

